

PG 8504 [AD] Laboratory dishwasher with AD-water supply.



- Perf./cycle, e.g. 64 narrow necked/ lab glassware w/ injectors
- Efficient use of resources variable speed heater pump
- Dispense process chemicals easily: Powder dispenser in the door
- With DI water connection final rinse with DI water

EAN: 4002515565261 / Material number: 10096780 / Old Material Number: 62850421GB

| Construction type and design  |   |
|---|---|
| Construction type and design  Construction type   | Freestanding, can be built-   |
| Construction type   | under, slim   |
| Casing  | Stainless steel   |
| Can be built-under  | •   |
| Electric door lock  | •   |
| Buzzer, acoustic signal at end of programme   | •   |
| Service-friendly design   | •   |
| Application   |   |
| Suitable for laboratories   | •   |
| Capacity  |   |
| Narrow-necked glassware per cycle [number]  | 64  |
| Performance data  |   |
| Circulation pump, Qmax in I/min   | 500   |
| Tested operating hours  | 15000   |
| Maximum final rinse temperature in °C   | 70  |
| Wash cabinet usable capacity in I   | 145.00  |
| Controls  |   |
| Control type  | TouchControl  |
| Programme selection   | Touch on metal  |
| Direct-access pushbuttons   | •   |
| Max. delay start in h   | 24  |
| Programmability   | programmable  |
| Programmes [number]   | 6   |
| Free programme positions [number]   | 2   |
| Automatic programme restart   | •   |
|   |   |
| Time left display   | •   |
| Time left display  Programme sequence display   | •   |
|   | - <del>-</del>  |
| Programme sequence display  | - <del>-</del>  |
| Programme sequence display Selectable display languages   | - <del>-</del>  |
| Programme sequence display Selectable display languages Standard electrical connection  | AC 230V 50HZ<br>1.70  |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection  | •<br>•<br>AC 230V 50HZ  |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A   | AC 230V 50HZ  1.70  2.40  13  |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m   | AC 230V 50HZ  1.70  2.40  |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage   | AC 230V 50HZ  1.70  2.40  13  |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m   | AC 230V 50HZ  1.70  2.40  13  |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number]   | AC 230V 50HZ 1.70 2.40 13 1.90  |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa   | AC 230V 50HZ  1.70  2.40  13  1.90  1  200-1000   |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm  | AC 230V 50HZ  1.70  2.40  13  1.90  |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener  | • AC 230V 50HZ  1.70  2.40  13  1.90  1  200-1000  •  |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I  | • AC 230V 50HZ 1.70 2.40 13 1.90  1 1 200-1000 100 • 10.70                                    |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN]  | • AC 230V 50HZ 1.70 2.40 13 1.90  1 1 200-1000 100 • 10.70 22                                 |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system  | • AC 230V 50HZ 1.70 2.40 13 1.90  1 1 200-1000 100 • 10.70                                    |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system Dimensions and weight  | • AC 230V 50HZ  1.70 2.40  13 1.90  1 1 200-1000 100 • 10.70 22 Waterproof system             |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system Dimensions and weight External dimensions, net height in mm  | • AC 230V 50HZ  1.70 2.40 13 1.90  1 1 200-1000 100 • 10.70 22 Waterproof system  835         |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm                   | • AC 230V 50HZ  1.70 2.40  13 1.90  1 1 200-1000 100 • 10.70 22 Waterproof system  835 600    |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm   | • AC 230V 50HZ  1.70 2.40 13 1.90  1 1 200-1000 100 • 10.70 22 Waterproof system  835         |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm External dimensions, gross height in mm | • AC 230V 50HZ  1.70 2.40  13 1.90  1 1 200-1000 100 • 10.70 22 Waterproof system  835 600    |
| Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm   | • AC 230V 50HZ  1.70 2.40 13 1.90  1 1 200-1000 100 • 10.70 22 Waterproof system  835 600 600 |



## PG 8504 [AD] Laboratory dishwasher with AD-water supply.



EAN: 4002515565261 / Material number: 10096780 / Old Material Number: 62850421GB

| External dimensions, gross depth in mm                           | 745                 |
|--|---------------------|
| Wash cabinet, usable height in mm                                | 520                 |
| Wash cabinet, usable width in mm                                 | 530                 |
| Wash cabinet, depth of upper basket in mm                        | 474                 |
| Wash cabinet, depth of lower basket in mm                        | 520                 |
| Net weight in kg   | 72                  |
| Gross weight in kg   | 79                  |
| Maximum floor load in N  | 1200                |
| Emissions data   |                     |
| Emission sound pressure level in the workplace                   | <70 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h                           | 1.10                |
| Features   |                     |
| Extensive components (option)                                    | •                   |
| Programmes   |                     |
| Short  | •                   |
| Medium   | •                   |
| Long   | •                   |
| Features   |                     |
| 1 door dispenser for rinsing agent                               | •                   |
| 1 door dispenser for powder cleaning agent                       | •                   |
| Multi-component filter system                                    | •                   |
| Variable-speed heater pump                                       | •                   |
| Load carrier – direct coupling                                   | •                   |
| In-door salt container   | •                   |
| Customer Service interface                                       | •                   |
| Wash cabinet seamlessly welded using laser technology            | •                   |
| Heater elements outside wash cabinet                             | •                   |
| Wash cabinet made from high-quality stainless steel (1.4301/304) | •                   |
| Connection options   |                     |
| External dispensing modules                                      | •                   |
| Standards, test certificates and symbols                         |                     |
| VDE (electrical safety)  | •                   |
| IP safety class according to EN 60529: IP 21                     | •                   |
| EN 61010-1   | •                   |
| EN 61010-2-040   | •                   |
| RoHS guideline 2011/65/EU  | •                   |
| WRAS   | •                   |
| Machinery Directive 2006/42/EC                                   | •                   |
| Madimory Bridding 2000/72/20                                     |                     |