

PG 8504 [ADP] Laboratory dishwasher with feed pump for AD water.



- Perf./cycle, e.g. 64 narrow necked/ lab glassware w/ injectors
- Efficient use of resources variable speed heater pump
- Dispense process chemicals easily: Powder dispenser in the door
- Pump for DI water: final rinse with fully demineralised water

EAN: 4002515565285 / Material number: 10096790 / Old Material Number: 62850422GB

Construction type and decign	
Construction type and design	Erocetanding, can be built
Construction type	Freestanding, can be built- under, slim
Casing	Stainless steel
Can be built-under	•
Electric door lock	•
Buzzer, acoustic signal at end of programme	•
Service-friendly design	•
Application	
Suitable for laboratories	•
Capacity	
Narrow-necked glassware per cycle [number]	64
Performance data	
Circulation pump, Qmax in I/min	500
Tested operating hours	15000
Maximum final rinse temperature in °C	70
Wash cabinet usable capacity in I	145.00
Controls	
Control type	TouchControl
Programme selection	Touch on metal
Direct-access pushbuttons	•
Max. delay start in h	24
Programmability	programmable
Programmes [number]	6
Free programme positions [number]	2
A. danadia ana ana ana ana ana ana	•
Automatic programme restart	•
Time left display	•
· •	. ————
Time left display	•
Time left display Programme sequence display	•
Time left display Programme sequence display Selectable display languages	•
Time left display Programme sequence display Selectable display languages Standard electrical connection	•
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection	• • • AC 230V 50HZ
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW	AC 230V 50HZ 1.70
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW	AC 230V 50HZ 1.70 2.40
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A	AC 230V 50HZ 1.70 2.40 13
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m	AC 230V 50HZ 1.70 2.40 13
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number]	AC 230V 50HZ 1.70 2.40 13 1.90
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number]	AC 230V 50HZ 1.70 2.40 13 1.90
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm	AC 230V 50HZ 1.70 2.40 13 1.90
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener	AC 230V 50HZ 1.70 2.40 13 1.90 1 1 200-1000
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm	AC 230V 50HZ 1.70 2.40 13 1.90 1 1 200-1000
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN]	AC 230V 50HZ 1.70 2.40 13 1.90 1 1 200-1000 100 • 10.70 22
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system	AC 230V 50HZ 1.70 2.40 13 1.90 1 1 200-1000 100 • 10.70
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/l Drain pump [DN] Water protection system Dimensions and weight	AC 230V 50HZ 1.70 2.40 13 1.90 1 1 200-1000 100 • 10.70 22
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system Dimensions and weight External dimensions, net height in mm	AC 230V 50HZ 1.70 2.40 13 1.90 1 1 200-1000 100 • 10.70 22
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system Dimensions and weight External dimensions, net height in mm External dimensions, net width in mm	AC 230V 50HZ 1.70 2.40 13 1.90 1 1 200-1000 100 • 10.70 22 Waterproof system
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm	AC 230V 50HZ 1.70 2.40 13 1.90 1 1 200-1000 100 • 10.70 22 Waterproof system 835
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/l Drain pump [DN] Water protection system Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm External dimensions, gross height in mm External dimensions, gross height in mm	AC 230V 50HZ 1.70 2.40 13 1.90 1 1 200-1000 100 10.70 22 Waterproof system 835 600 600 940
Time left display Programme sequence display Selectable display languages Standard electrical connection Electrical connection Electric heater rating in kW Total rated load in kW Fuse rating in A Length of mains connection cable in m Water connection/drainage Cold water [number] VEP – with feed pump for DI water [number] Required flow pressure in kPa Maximum delivery head for drain pump in cm Integrated water softener Maximum water hardness (cold water/hot water) in mmol/I Drain pump [DN] Water protection system Dimensions and weight External dimensions, net height in mm External dimensions, net depth in mm	AC 230V 50HZ 1.70 2.40 13 1.90 1 1 200-1000 100 • 10.70 22 Waterproof system 835 600 600



PG 8504 [ADP] Laboratory dishwasher with feed pump for AD water.



EAN: 4002515565285 / Material number: 10096790 / Old Material Number: 62850422GB

External dimensions, gross depth in mm	745
Wash cabinet, usable height in mm	520
Wash cabinet, usable width in mm	530
Wash cabinet, depth of upper basket in mm	474
Wash cabinet, depth of lower basket in mm	520
Net weight in kg	72
Gross weight in kg	79
Maximum floor load in N	1200
Emissions data	
Emission sound pressure level in the workplace	<70 dB(A) re 20 µPa
Heat dissipation into the room in MJ/h	1.10
Features	
Extensive components (option)	•
Programmes	
Short	•
Medium	•
Long	•
Features	
1 door dispenser for rinsing agent	•
1 door dispenser for powder cleaning agent	•
Multi-component filter system	•
Variable-speed heater pump	•
Load carrier – direct coupling	•
In-door salt container	•
Customer Service interface	•
Wash cabinet seamlessly welded using laser technology	•
Heater elements outside wash cabinet	•
Wash cabinet made from high-quality stainless steel	•
(1.4301/304)	
Connection options	
External dispensing modules	•
Standards, test certificates and symbols	
VDE (electrical safety)	<u>•</u>
IP safety class according to EN 60529: IP 21	<u>•</u>
EN 61010-1	<u>•</u>
EN 61010-2-040	<u>•</u>
RoHS guideline 2011/65/EU	<u>•</u>
WRAS	•
Machinery Directive 2006/42/EC	•